



eConnect™

Item.no: see page 3



Type 2

eConnect™

Designed for extreme conditions

Premium charging cables made for performance, durability and unmatched user-friendliness in any conditions. eConnect cables can be used to charge all vehicles with a Type 2 interface.

Made for Nordic conditions:

eConnect cables remain soft and flexible, even in severe cold.

User-friendly:

eConnect cables are lightweight and have plugs with universal ergonomic design.

Durable:

Our robust cables and terminals are made for long term use.



Smart cap:

The retractable cap prevents it from collecting water and dirt during charging and from bumping into the car.

Environmentally friendly:



Our cables and plugs are recyclable

Accessories:

eConnect is available with a wide range of accessories.

Check defa.com for latest selection.

Specification

Ratings	See Item no. table
IP rating, connected/with end cap	IP44
Operating temperature [°C]	-40 to +55
Storage temperature [°C]	-50 to +85
Charging cable type	Mode 3
Connection to vehicle	Type 2 
Connection to charging station	Type 2 
Certification	IEC 62196-1, IEC 62196-2 DEFA is certified to the requirements of IATF 16949, ISO 9001, ISO 14001 and ISO 45001.
Recycling	EE-waste

eConnect is available in the following versions:

Item no.	Current [A]*	Power [kW]*	Voltage [V~]*	Phase	Length [m]	Weight [kg]
711304	20	4,6	250	1	5,0	1,4
711305	20	4,6	250	1	7,5	1,8
711308	32	7,4	250	1	5,0	1,9
711309	32	7,4	250	1	7,5	2,4
711306	20	13,8	480	3	5,0	2,1
711307	20	13,8	480	3	7,5	2,7
711310	32	22,0	480	3	5,0	3,1
711311	32	22,0	480	3	7,5	4,0

***Maximum rating**

The actual charge rate is also determined by the onboard charger (car), the charging station and the temperature of the batteries.